



**Protecta**

The first full body harness - an excellent choice for turnaround, scaffold erection and general facility maintenance.

**PRODUCT CODE :** AB17510A, AB17530A



**Shock Absorbing Twin Webbing Lanyard**

Length: 2.0m max, Capacity: 140kg max, Limited Arresting Force: Below 6kN and with CE EN355 approval.

**Energy Absorbing Polyamide Twisted Rope Lanyard -**

PN 1390399 - [VSPL-RLE-3008-(T)]

**One Side Karabiner VSPL 1102 & Other Side Scaffold Hook**

**VSPL 1301**

Rope Material : 3 Strand Polypropylene

Diameter : 12mm

Length : 1.0m, 1.5m, 2.0m

Compliance : Conforms to EN 355

Attribute : Splices protected with a protective sleeve loops protected with a plastic thimble

**Double Polyamide Twisted Rope Lanyard with Energy**

Absorber - PN 1390398 - [VSPL-FRL-3501-(T)]

**Two Scaffold Hooks VSPL 1310 on either end & Karabiner**

**VSPL 1102 as anchorage element**

Rope Material : 3 strand Polyamide

Diameter : 12mm

Length : 1.5m

Compliance : Conforms to EN 355



VSPL-RLE-3008

VSPL-FRL-3501